





# Sun Tunnel Skylights®

Bright, Natural Light. Quick Installation.

# Fill Every Room with Natural Light

Daylight is powerful, which is why every room deserves to be filled with it. The VELUX Sun Tunnel Skylight's® versatile design offers guick and easy installation, letting you enjoy a new world of natural light in as soon as an afternoon.

## Meet Your Sun Tunnel Skylight®

**D** 

### **Clear UV Resistant Dome**

Captures the most light possible with a clear dome.



## 2 Adjustable Pitch Adapter

Pivots the tunnel towards the sun and allows for easier installation.




**One-Piece Metal Flashing** Provides maximum light capturing while guaranteeing no water penetration.



6

Adjustable Elbow (Rigid Tunnel) Rotates 45°. Elbows are 12" long.



## Offers quick and easy installation of tunnel.

Rigid Tunnel Option - 99% reflective, 24" sections assemble guickly with the Flexi Loc™ tunnel system.

Flexible Tunnel Option - Faster method of installation with seamless all-in-one elbow and tunnel system.

## Solar Night Light (Rigid Tunnel)

The Solar Night Light provides soft, soothing light when natural light isn't available.\* Optional add-on.

\*Must be purchased with sun tunnel to receive federal tax credit. \*\*Federal tax credit based off total product and installation cost. Visit veluxusa.com/go-solar



## Pre-Assembled Ceiling Ring

Diffuses light into the space using an energy-efficient, frosted dual-diffuser system. Diffuser options can be customized to meet décor and style.



VELUX Sun Tunnel Skylights<sup>®</sup> fit between ceiling beams, allowing sunlight to travel from the roof to the space below uninhibited.





# Choosing Your Sun Tunnel Skylight<sup>®</sup>

There are several sun tunnel options for you to choose from, but picking one for your home doesn't have to be complicated. We'll make it easy!


## Two Types of Tunnels

### **Rigid Tunnels**

- Designed as a highly reflective tunnel, the rigid tunnel lets in the most light
- Enables longer runs
- Excellent for areas with less sunlight
- Easy assembly of tunnel with Flexi Loc<sup>™</sup> system

### Flexible Tunnels

- The flexible sun tunnel is movable and able to bend around tight, obstructed spaces
- Fast and easy installation
- Softens and provides
  additional light diffusion
- Excellent for sunny areas and short runs





10", 14", & 22" Model TGR

### Low-Profile Metal Flashing:

- · Best for south, west, and east-facing roofs
- Parallel to roof and designed to blend with roofline



#### Pitched Metal Flashing:

- Provides consistent light distribution throughout the day
- Provides straighter tunnel run through many different roof pitches



#### Low-Profile Flat Glass Flashing: (Available in 14" only)

- Low-profile glass design creates sleek appearance
- Perfect for developments where local ordinances do not allow acrylic domes on the roof



#### Curb Metal Flashing: (Available in 14" only)

- One-piece metal curb-mounted flashing
- Ideal for low roof slopes and/or tile roofing applications



#### Decorative Diffuser Options: (Available in 10" & 14" only)

• Select from a range of micro-engineered decorative diffusers to increase interior aesthetics and visual appeal.

## Accessories

## Sun Tunnel Skylight Accessories

#### NEW

The VELUX Sun Tunnel Solar Night Light



Produces constant, low-level light after the sun sets so you can enjoy light day and night. *Available for all residential rigid sun tunnels*.

\*Tax credit based off total installation cost. Visit veluxusa.com/go-solar

#### Universal Electric Light Kit (ZTL)

#### Daylight Controller (ZTP) Power Supply (ZZZ 233)



Allows the user to control the amount of daylight that enters a room. Perfect for rooms that require room darkening. *Available in 14" & 22" rigid tunnels.* 

#### Vapor Barrier (ZTY)



Energy efficient electric light with a GU24 base designed for residential sun tunnels. Easy installation and compatible with energy efficient CFL and LED bulbs. *GU24 bulb sold separately*.



Molded, impermeable, thin vapor barrier sheet prevents moisture from penetrating ceiling opening. Recommended for new installations in cold climates.

#### Energy Kit (ZTC)



Designed to increase the energy efficiency of the VELUX Sun Tunnel Skylight while enabling it to be ENERGY STAR<sup>®</sup> certified.

Diffusion Enhancer (ZTZ 209)



A highly reflective, obscure 6" band designed to diffuse direct sunlight.

#### Rigid Tube (ZTR)



Additional 24" tube section when tunnel length exceeds 48". *Available in bulk quantities*.

#### Suspension Wire kit (ZTZ 203)



12-gauge wire and fastener set to secure longer tunnel sections.

#### Elbows (ZTE)



Durable, interchangeable 45° elbows that are 12" long and come in 3 diameters. Multiple elbows can be joined together with rotating couplers.

#### Rotating Coupler (ZTZ 211)



Easy to install tunnel and elbow coupler that enables quick tunnel connections. Rotating joint helps align tunnel sections.

#### Pitched Tile Flashing (ZTM)



Painted, malleable, aluminum sheet provides a water-tight flashing without the use of sealants. *Available for 10" and 14"*.

#### Curb-mounted Tile Flashing (ECW)



Pliable, pleated, curb-mounted tile flashing system engineered for tile roofing material. *Available for 14"*.

# Product Details

## **Rigid Units Include:**

- Flashing complete with dome
- Two 12" elbows
- 24" extension
- Ceiling diffuser assembly complete with frosted diffuser

## Flexible Units Include:

- Flashing complete with dome
- 8' of tunnel for 14" units
- 12' of tunnel for 22" units
- Ceiling diffuser assembly complete with frosted diffuser

Note: Additional tunnel available as needed

### Square Footage Recommendations:

- 10" Rigid (TGR/TMR) up to 200 sq.ft.
- 14" Rigid (TGR/TMR/TLR/TCR) up to 325 sq.ft.
- 22" Rigid (TGR) up to 625 sq.ft.
- 14" Flex (TGF/TMF) up to 150 sq.ft.
- 22" Flex (TGF) up to 325 sq.ft.

Note: These are all general guidelines. Sun angles, length of tunnel, roof orientation, tunnel straightness, and room consideration may affect this number.

## Maximum Tunnel Length Recommendations:

- Rigid 10" is 20' and 14" is 30' (TGR/TMR/TLR/TCR)
- Rigid 22" is 40' (TGR)
- Flex 14" (TGF/TMF) is 8'
- Flex 22" (TGF) is 12'

Note: Orientation of roof and straightness of tunnel are both important factors.

## Other Options:

- Impact models (for hurricane prone areas)
- Commercial Sun Tunnel Skylights for school and industrial applications